

4" MEDIUM DUTY									
MODEL #	HEIGHT (FT)	LENGTH (FT)	PIPE CLEARANCE	WEIGHT (LBS)	PSF	MAX DEPTH RATING (FT)			
						A25	B45	C60	C80
XTS-4M-412	4	12	16"	3,409	2,627	52	52	44	34
XTS-4M-416	4	16	16"	4,248	1,395	52	33	24	20
XTS-4M-420	4	20	16"	5,086	965	34	20	15	12
XTS-4M-424	4	24	16"	5,925	588	24	14	12	10

4" MEDIUM DUTY									
MODEL #	HEIGHT (FT)	LENGTH (FT)	PIPE CLEARANCE	WEIGHT (LBS)	PSF	MAX DEPTH RATING (FT)			
						A25	B45	C60	C80
XTS-4M-612	6	12	40"	4,574	2,635	52	52	45	35
XTS-4M-616	6	16	40"	5,771	1,399	52	33	25	20
XTS-4M-618	6	18	40"	6,369	1,088	45	26	20	16
XTS-4M-620	6	20	40"	6,968	870	36	21	18	13
XTS-4M-624	6	24	40"	8,164	596	25	15	12	10

4" MEDIUM DUTY									
MODEL #	HEIGHT (FT)	LENGTH (FT)	PIPE CLEARANCE	WEIGHT (LBS)	PSF	MAX DEPTH RATING (FT)			
						A25	B45	C60	C80
XTS-4M-88	8	13	64"	4,146	2,645	52	52	46	36
XTS-4M-810	8	10	64"	4,924	2,120	52	52	41	31
XTS-4M-812	8	12	64"	5,701	1,771	52	44	34	26
XTS-4M-816	8	16	64"	7,165	1,339	52	34	24	20
XTS-4M-820	8	20	64"	8,726	965	38	23	20	14
XTS-4M-824	8	24	64"	10,366	597	26	17	14	10

4" MEDIUM DUTY									
MODEL #	HEIGHT (FT)	LENGTH (FT)	PIPE CLEARANCE	WEIGHT (LBS)	PSF	MAX DEPTH RATING (FT)			
						A25	B45	C60	C80
XTS-4M-1010	10	10	84"	6,173	1,631	52	41	31	25
XTS-4M-1012	10	12	84"	7,131	1,391	52	34	27	21
XTS-4M-1016	10	16	84"	9,046	973	42	26	18	17
XTS-4M-1020	10	20	84"	10,216	779	35	22	16	14
XTS-4M-1024	10	24	84"	11,107	536	26	17	15	12