

6" HEAVY DUTY									
MODEL NUMBER	HEIGHT (FT)	LENGTH (FT)	PIPE CLEARANCE	WEIGHT (LBS)	PSF	MAX DEPTH RATING (FT)			
						A25	B45	C60	C80
XTS-6H-416	4	16	16"	5,296	3,141	52	52	52	40
XTS-6H-420	4	20	16"	6,408	1,940	52	44	34	25
XTS-6H-424	4	24	16"	7,519	1,316	52	30	24	18
XTS-6H-426	4	26	16"	8,074	1,111	45	26	20	15
XTS-6H-428	4	28	16"	8,630	950	39	22	17	13

6" HEAVY DUTY									
MODEL #	HEIGHT (FT)	LENGTH (FT)	PIPE CLEARANCE	WEIGHT (LBS)	PSF	MAX DEPTH RATING (FT)			
						A25	B45	C60	C80
XTS-6H-616	6	16	40"	7,310	3,140	52	52	52	41
XTS-6H-620	6	20	40"	8,900	1,939	52	43	34	26
XTS-6H-624	6	24	40"	10,489	1,315	52	30	25	19
XTS-6H-626	6	26	40"	11,284	1,110	46	26	20	16
XTS-6H-628	6	28	40"	12,079	950	40	22	19	14

6" HEAVY DUTY									
MODEL #	HEIGHT (FT)	LENGTH (FT)	PIPE CLEARANCE	WEIGHT (LBS)	PSF	MAX DEPTH RATING (FT)			
						A25	B45	C60	C80
XTS-6H-816	8	16	64"	9,222	2,350	52	52	42	32
XTS-6H-820	8	20	64"	11,290	1,858	52	43	33	25
XTS-6H-824	8	24	64"	13,275	1,313	52	32	24	19
XTS-6H-826	8	26	64"	14,692	1,108	47	28	21	17
XTS-6H-828	8	28	64"	15,426	948	40	25	20	15

6" HEAVY DUTY									
MODEL #	HEIGHT (FT)	LENGTH (FT)	PIPE CLEARANCE	WEIGHT (LBS)	PSF	MAX DEPTH RATING (FT)			
						A25	B45	C60	C80
XTS-6H-1016	10	16	84"	11,634	2,097	52	52	41	30
XTS-6H-1020	10	20	84"	14,180	1,677	52	40	31	24
XTS-6H-1024	10	24	84"	17,727	1,310	52	33	25	20
XTS-6H-1026	10	26	84"	18,000	1,106	48	30	22	18
XTS-6H-1028	10	28	84"	19,273	947	41	24	20	16