

6" MEDIUM DUTY									
MODEL #	HEIGHT (FT)	LENGTH (FT)	PIPE CLEARANCE	WEIGHT (LBS)	PSF	MAX DEPTH RATING (FT)			
						A25	B45	C60	C80
XTS-6M-416	4	16	16"	4,644	2,253	52	52	37	29
XTS-6M-420	4	20	16"	5,591	1,398	52	32	23	19
XTS-6M-424	4	24	16"	6,539	956	38	22	16	13
XTS-6M-426	4	26	16"	7,013	800	33	19	14	12
XTS-6M-428	4	28	16"	7,487	687	28	17	12	10

6" MEDIUM DUTY									
MODEL #	HEIGHT (FT)	LENGTH (FT)	PIPE CLEARANCE	WEIGHT (LBS)	PSF	MAX DEPTH RATING (FT)			
						A25	B45	C60	C80
XTS-6M-616	6	16	40"	6,367	2,249	52	52	38	30
XTS-6M-620	6	20	40"	7,712	1,391	52	33	24	20
XTS-6M-624	6	24	40"	9,057	945	39	23	18	14
XTS-6M-626	6	26	40"	9,729	800	33	20	15	13
XTS-6M-628	6	28	40"	10,401	682	29	17	12	10

6" MEDIUM DUTY									
MODEL #	HEIGHT (FT)	LENGTH (FT)	PIPE CLEARANCE	WEIGHT (LBS)	PSF	MAX DEPTH RATING (FT)			
						A25	B45	C60	C80
XTS-6M-816	8	16	64"	8,255	2,150	52	52	38	30
XTS-6M-820	8	20	64"	9,902	1,390	52	35	25	21
XTS-6M-824	8	24	64"	11,444	945	40	25	18	14
XTS-6M-826	8	26	64"	12,314	799	35	21	16	15
XTS-6M-828	8	28	64"	13,185	729	30	18	15	12

6" MEDIUM DUTY									
MODEL #	HEIGHT (FT)	LENGTH (FT)	PIPE CLEARANCE	WEIGHT (LBS)	PSF	MAX DEPTH RATING (FT)			
						A25	B45	C60	C80
XTS-6M-1016	10	16	84"	10,330	2,094	52	50	36	30
XTS-6M-1020	10	20	84"	12,135	1,224	52	32	24	20
XTS-6M-1024	10	24	84"	14,274	940	41	24	21	15
XTS-6M-1026	10	26	84"	15,343	791	35	22	18	14
XTS-6M-1028	10	28	84"	16,412	679	31	19	15	13